



1-888-456-8008

## CUSTOM COLOR CAULK SANDED

### Description:

Grout Direct Custom Colored Caulk is a silicone acrylic caulk specially formulated to produce a flexible waterproof seal. It is a fast set formula that can be Color Sealed in 30 minutes.

### Uses:

Use on sanded and unsanded grout joints, counter-tops, wall joints, pipes, ceramic, moldings, baseboard and any other caulkable surface.

### Coverage:

A 1/4" bead = 30 linear feet. Coverage depends on surface texture, porosity and depth of opening.

### Preparation:

Remove all dirt, mildew, wax, sealers, silicone, grease, cleaner residue, efflorescence, dust and foreign matter to provide a clean sound substrate. The surface should be allowed to dry for a minimum of 2 hours prior to application of the caulk. A neutral PH cleaner or floor stripper should be used. A final rinse with clean fresh water is required to remove all residue. To remove some sealers, an aggressive industrial stripper may be required.

### Pre-application:

**CUSTOM COLORED CAULK ALWAYS GOES ON SEVERAL SHADES LIGHTER THAN THE ACTUAL COLOR. CUSTOM COLORED CAULK WILL MATCH COLOR SEAL AFTER 12 HOURS OF DRY TIME.** Always apply a test area to determine the suitability of this product. It is the sole responsibility of the applicator to determine that the surface is free of dirt, mildew, cleaner residue, wax, sealers, silicone, grease and any foreign material that could inhibit adhesion of the sealer. New grout installations should be allowed to cure for 48 hours prior to caulking.

### Application:

Read the entire label, this data sheet and the MSDS sheet prior to using custom colored caulk. Cut tip at a 45 degree angle to desired bead size; 1/8" minimum. With a standard caulk gun, apply consistent trigger pressure forcing the caulk into the surface. Smooth caulk with a wet finger or tool. Clean the excess with a damp rag or chamois. Allow caulk to dry for 30 minutes before sealing with Color Seal. If caulk is used on a foot traffic surface, Color Seal must be used as a top-coat.

### Dry Time:

Dry to the touch is 30 min. to 2 hours depending on temperature, humidity and porosity. A partial cure is 8 to 24 hours. A full cure is 8 days. Do not attempt to use any cleaners until Caulk is fully cured.

### Clean-up:

Clean tools and wiping cloths with clean water. For final clean-up use warm soapy water.

### Technical Assistance:

1-888-456-8008